

Increased output with added features, the C1D1 safety rated Survivor X right-angle light is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



No tools needed to change batteries

New charger design:

- Survivor X securely locks into the charger - fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



Rubber dome push-button switch easy to use with gloves
Features battery life indicator

Battery life indicator in switch:
 – Green indicates full charge
 – Turns red when battery is nearing low voltage
 – Flashes red continuously when 15 minutes left of battery life

Unbreakable polycarbonate lens with silicone anti-scratch coating
Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible



High, low and emergency flash modes: – High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-Ion); runs 5 hours (alkaline) – Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-Ion); runs 15 hours (alkaline) – Flash for signaling: runs 8 hours Optimized electronics provide regulated intensity
IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested
Uses rechargeable lithium ion battery (charges in 5 hours) or three alkaline batteries
7.06 in. (17.92 cm); Li-Ion: 12.2 oz (346g); Alkaline: 12.8 oz (363g)

Class I & II, Division 1, Groups A,B,C,D,E,F,G; Class III, T-Code: T3/T4		
Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)		
Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position		
Limited Lifetime Warranty Visit streamlight.com for full warranty information		
Description	Orange	Yellow
Survivor X - 120V/100V AC/12V DC	#90952	#90962
Survivor X - 230V AC/12V DC	#90953	#90963
Survivor X - Alkaline	#90950	#90960