

TUL300 TIANLI



TUL300



Size	Type	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/inch)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/lbs)	Speed (Km/mph)
15.5R25	TL	12.00/1.3	E-3/L-3	152/B	★	24.4 31/32	1275 50.2	405 15.9	375 54	3550 7826	50 30
				169/A2	★	24.4 31/32	1275 50.2	405 15.9	500 73	5800 12787	10 6
17.5R25	TL	14.00/1.5	E-3/L-3	167/B	★★	27 34/32	1347 53.0	449 17.7	525 76	5450 12015	50 30
				182/A2	★★	27 34/32	1347 53.0	449 17.7	650 94	8500 18739	10 6
20.5R25	TL	17.00/3.5	E-3/L-3	177/B	★★	31 39/32	1482 58.3	533 21.0	525 76	7300 16093	50 30
				193/A2	★★	31 39/32	1482 58.3	533 21.0	650 94	11500 25353	10 6
			IND-3	198/A2	★★★	31 39/32	1482 58.3	533 21.0	800 116	13200 29101	10 6
				206/A2	★★★	41 52/32	1602 63.1	607 23.9	525 76	9250 20392	50 30
23.5R25	TL	19.50/4.0	E-3/L-3	185/B	★★	41 52/32	1602 63.1	607 23.9	650 94	14500 31966	10 6
				201/A2	★★	41 52/32	1602 63.1	607 23.9	800 116	17000 37478	10 6
			IND-3	206/A2	★★★	41 52/32	1602 63.1	607 23.9	800 116	17000 37478	10 6
				214/A2	★★★	48/32	1735 68.3	686 27.0	525 76	11500 25353	50 30
26.5R25	TL	22.00/4.5	E-3/L-3	193/B	★★	38 48/32	1735 68.3	686 27.0	525 76	11500 25353	50 30
				209/A2	★★	38 48/32	1735 68.3	686 27.0	650 94	18500 40785	10 6
			IND-3	214/A2	★★★	38 48/32	1735 68.3	686 27.0	800 116	21200 46737	10 6
				216/A2	★★	45 57/32	1860 73.2	769 30.3	525 76	14000 30864	50 30
29.5R25	TL	25.00/3.5	E-3/L-3	200/B	★★	45 57/32	1860 73.2	769 30.3	650 94	22400 49383	10 6
				216/A2	★★	45 57/32	1860 73.2	769 30.3	650 94	22400 49383	10 6